# SB5560HDi



# 55" Signature Series True Outdoor All-Weather LCD Television for permanent outdoor installation

- Bright 55" Full HD 1080p 120 Hz LCD screen for improved outdoor viewing
- Exterior designed to protect internal components from rain, dust, insects, humidity, and salt air
- Multi-fan airflow system keeps the unit cool and dry in temperatures up to 50°C
- Ability to operate in cold weather (-31°C)
- RS232 serial control with discrete on, off, and input control (located in the cable-entry compartment)
- Rear IR receiver (located in the cable-entry compartment)
- Innovative water-tight Cable Entry System seals out moisture and allows for easy hook-ups
- ASA outdoor rated high-impact resin exterior
- Weatherproof built in 20W speakers
- Weatherproof remote control
- Weatherproof control buttons
- Remote Control Lock-Out prevents unauthorized users from changing the programming

#### SCREEN

LCD Screen55-inch diagonal TFT Active Matrix LCDResolution1920 x 1080 Full-HD 1080pAspect Ratio16:9Contrast Ratio5000:1Frame Rate120 HzViewing Angle176° x 176°Response Time6.5 millisecondsTV formats1080p, 1080i, 720p, 576p, 576i		
Aspect Ratio16:9Contrast Ratio5000:1Frame Rate120 HzViewing Angle176° x 176°Response Time6.5 milliseconds	LCD Screen	55-inch diagonal TFT Active Matrix LCD
Contrast Ratio5000:1Frame Rate120 HzViewing Angle176° x 176°Response Time6.5 milliseconds	Resolution	1920 x 1080 Full-HD 1080p
Frame Rate120 HzViewing Angle176° x 176°Response Time6.5 milliseconds	Aspect Ratio	16:9
Viewing Angle176° x 176°Response Time6.5 milliseconds	Contrast Ratio	5000:1
Response Time 6.5 milliseconds	Frame Rate	120 Hz
	Viewing Angle	176° x 176°
TV formats 1080p, 1080i, 720p, 576p, 576i	Response Time	6.5 milliseconds
	TV formats	1080p, 1080i, 720p, 576p, 576i

#### **PHYSICAL SPECS**

Accessories Included	Weatherproof remote control and outdoor dust cover
Exterior	Resin
Exterior colour	Silver
TV Dimensions (cm)	135.6 W x 86 H x 18.5 D
TV Weight	49 kg
Shipping Dimensions (cm)	152.4 W x 116.8 H x 33 D
Shipping Weight	58 kg
Warranty	One-year parts and labour



## CONNECTIONS

RF	Antenna/CATV (ATSC/QAM/NTSC) x 1
HDMI	HDMI™ Input x 2
Video Composite	S-Video x 1 and Composite Video x 1, L/R Audio Inputs x 1
Video Component	YPbPr plus Stereo Audio x 2
PC	15-pin D-sub VGA plus Stereo Audio
Control Set	RS232 Serial, Discrete IR Control, Concealed IR Window
Audio Out	SPDIF Audio, Analog 3.5mm headphone jack
Speakers	20 watt built in speakers
Input Power	100-240 VAC, 50-60 Hz 4.0 A Max

### **TEMPERATURE TOLERANCES**

Operating Temp	-31° to 50°C
Non-op. Temp	-31° to 60°C*

\*Off mode with power applied. The non-operating temperature feature requires power to be applied. Specifications are subject to change without notice.