

SB6560HDi



65" Signature Series True Outdoor All-Weather LED Television for permanent outdoor installation

- Bright 65" Full HD 1080p 240 Hz LED screen for improved outdoor viewing
- Exterior designed to protect internal components from rain, dust, insects, humidity, and salt air
- Multi-fan airflow system keeps the unit cool and dry in temperatures up to 50°C
- Ability to operate in cold weather (-31°C)
- RS232 serial control with discrete on, off, and input control (located in the cable-entry compartment)
- Rear IR receiver (located in the cable-entry compartment)
- Innovative water-tight Cable Entry System seals out moisture and allows for easy hook-ups
- Powdercoated aluminium exterior
- Weatherproof detachable 20W speaker module
- Weatherproof remote control
- Weatherproof control buttons
- Remote Control Lock-out prevents unauthorized users from changing the programming



SCREEN

| | |
|----------------|--|
| LED Screen | 65-inch diagonal TFT Active Matrix LED |
| Resolution | 1920 x 1080 Full-HD 1080p |
| Aspect Ratio | 16:9 |
| Contrast Ratio | 5000:1 |
| Frame Rate | 240 Hz |
| Viewing Angle | 176° x 176° |
| Response Time | 6.5 milliseconds |
| TV formats | 1080p, 1080i, 720p, 576p, 576i |

PHYSICAL SPECS

| | |
|--------------------------|--|
| Accessories Included | Weatherproof remote control and outdoor dust cover |
| Exterior | Powdercoated aluminium |
| Exterior colour | Silver |
| TV Dimensions (cm) | 154 W x 91 H x 19 D |
| TV Weight | 49 kg |
| Shipping Dimensions (cm) | 173 W x 122 H x 33 D |
| Shipping Weight | 58 kg |
| Warranty | One-year parts and labour |

CONNECTIONS

| | |
|-----------------|---|
| RF | Antenna/CATV (ATSC/QAM/NTSC) x 1 |
| HDMI | HDMI™ Input x 4 |
| Video Composite | S-Video x 1 and Composite Video x 1, L/R Audio Inputs x 1 |
| Video Component | YPbPr plus Stereo Audio x 2 |
| PC | 15-pin D-sub VGA plus Stereo Audio |
| Control Set | RS232 Serial, Discrete IR Control, Concealed IR Window |
| Audio Out | TosLink Digital Optical x 1, Analog 3.5mm headphone jack |
| Speakers | 20 watt detachable speaker module |
| Input Power | 100-240 VAC, 50-60 Hz 4.0 A Max |

TEMPERATURE TOLERANCES

| | |
|----------------|---------------|
| Operating Temp | -31° to 50°C |
| Non-op. Temp | -31° to 60°C* |

*Off mode with power applied. The non-operating temperature feature requires power to be applied. Specifications are subject to change without notice.