

SB4707ESTL



47" Marquee Series True Outdoor All-Weather Digital Signage Display

- Landscape installation only, for portrait installation use SB4707ESTP
- Direct Sunlight-Readable 700 NIT LCD screen.
- High temperature Enhanced Solar Tolerance (EST) technology prevents isotropic blackout.
- Exterior designed to protect internal components from rain, dust, insects, humidity, and salt air.
- Multi-fan airflow system keeps the unit cool and dry in temperatures up to 50°C.
- Ability to operate in cold weather (-31°C).
- Front tempered anti-reflective glass window provides added protection to LCD screen, and safeguards against vandalism and abuse.
- Full command control, RS232 and Discrete IR located in cable-entry compartment.
- Innovative water-tight Cable Entry System seals out moisture and allows for easy hook-ups.
- Internal media compartment to house DMP, Pro:Idiom boxes, or fan-less PC's (optional).
- Powder-coated aluminium exterior.
- Weatherproof detachable 20W speaker module (optional).
- Weatherproof remote control.
- Weatherproof control buttons.
- Remote Control Lock-Out prevents unauthorised users from changing the programming.



Shown in Black with Optional Speakers

SCREEN

LCD Screen	47-inch diagonal TFT Active Matrix
Resolution	1920 x 1080 Full-HD 1080p
Screen Brightness	700 nit
Aspect Ratio	16:9
Contrast Ratio	4000:1
Frame Rate	60 Hz
Viewing Angle	176° x 176°
Response Time	9.0 milliseconds
TV formats	1080p, 1080i, 720p, 480p, 480i

PHYSICAL SPECS

Accessories Included	Weatherproof remote control
Exterior	Powder-coated aluminium
Exterior colour	Silver, Black
TV Dimensions (cm)	113.6 W x 74.5 H x 17.4 D
TV Weight	31.75 kg
Shipping Dimensions (cm)	132.1 W x 106.7 H x 33 D
Shipping Weight	56.7 kg
Warranty	One-year parts and labour

CONNECTIONS

RF	Antenna/CATV (ATSC/QAM/NTSC) x 1
HDMI	HDMI™ Input x 4
Video Composite	S-Video x 1, Composite Video x 1, L/R Audio Inputs x 1
Video Component	YPbPr plus Stereo Audio x 2
PC	15-pin D-sub VGA plus Stereo Audio
Control Set	RS232 Serial, Discrete IR Control, Concealed IR Window
Audio Out	TosLink Digital Optical x 1, Analog 3.5mm headphone jack
Speakers	20 watt detachable speaker module (optional)
Input Power	100-240 VAC, 50-60 Hz 4.0 A Max

TEMPERATURE TOLERANCES

Operating Temp	-31° to 50°C
Non-op. Temp	-31° to 60°C*

*Off mode with power applied. The non-operating temperature feature requires power to be applied. Specifications are subject to change without notice.