

SB5507ESTL



55" Marquee Series True Outdoor All-Weather Digital Signage Display

- Landscape installation only, for portrait installation use SB5507ESTP
- Direct Sunlight-Readable 700 NIT LCD screen.
- High temperature Enhanced Solar Tolerance (EST) technology prevents isotropic blackout.
- Exterior designed to protect internal components from rain, dust, insects, humidity, and salt air.
- Multi-fan airflow system keeps the unit cool and dry in temperatures up to 50°C.
- Ability to operate in cold weather (-31°C).
- Front tempered anti-reflective glass window provides added protection to LCD screen, and safeguards against vandalism and abuse.
- Full command control, RS232 and Discrete IR located in cable-entry compartment.
- Innovative water-tight Cable Entry System seals out moisture and allows for easy hook-ups.
- Internal media compartment to house DMP, Pro:Idiom boxes, or fan-less PC's (optional).
- Powder-coated aluminium exterior.
- Weatherproof detachable 20W speaker module (optional).
- Weatherproof remote control.
- Weatherproof control buttons.
- Remote Control Lock-Out prevents unauthorised users from changing the programming.



Shown in Black with Optional Speakers

SCREEN

LCD Screen	55-inch diagonal TFT Active Matrix
Resolution	1920 x 1080 Full-HD 1080p
Screen Brightness	700 nit
Aspect Ratio	16:9
Contrast Ratio	5000:1
Frame Rate	120 Hz
Viewing Angle	176° x 176°
Response Time	10 milliseconds
TV formats	1080p, 1080i, 720p, 480p, 480i

PHYSICAL SPECS

Accessories Included	Weatherproof remote control
Exterior	Powder-coated aluminium
Exterior colour	Silver, Black
TV Dimensions (cm)	133.2 W x 85.3 H x 19.8 D
TV Weight	52 kg
Shipping Dimensions (cm)	152.4 W x 116.8 H x 33 D
Shipping Weight	61 kg
Warranty	One-year parts and labour

CONNECTIONS

RF	Antenna/CATV (ATSC/QAM/NTSC) x 1
HDMI	HDMI™ Input x 2
Video Composite	S-Video x 1, Composite Video x 1, L/R Audio Inputs x 1
Video Component	YPbPr plus Stereo Audio x 2
PC	15-pin D-sub VGA plus Stereo Audio
Control Set	RS232 Serial, Discrete IR Control, Concealed IR Window
Audio Out	SPDIF Audio, Analog 3.5mm headphone jack
Speakers	20 watt detachable speaker module (optional)
Input Power	100-240 VAC, 50-60 Hz 4.0 A Max

TEMPERATURE TOLERANCES

Operating Temp	-31° to 50°C
Non-op. Temp	-31° to 60°C*

*Off mode with power applied. The non-operating temperature feature requires power to be applied. Specifications are subject to change without notice.