

Specifications

Specifications	
LCD Screen	31.5-inch (800.1mm) diagonal TFT Active Matrix
Resolution	1366 x 768
Aspect Ratio	16:9
Contrast Ratio	3000:1
H/V Viewing Angle	178° by 178°
Response Time	6.5 milliseconds
TV formats	1080i, 720p, 480i, 480p
Input Connectors:	
RF	Antenna/CATV (NTSC/ATSC/QAM)
HDMI	HDMI Input x2
Video Composite	S-Video x1 and Composite Video x1, L/R Audio Inputs x1
Video Component	YCbCr/YPbPr x2 and audio L/R channels x2
PC	15-pin D-sub VGA plus Stereo Audio
Control Set	RS232 Serial, Discrete IR Control, Concealed IR Window
Audio Out	SPDIF Audio, Analog Headphone Jack
Speakers	10-watt x 2 channels, water-resistant detachable speaker module
Exterior	Powder-coated aluminum
Input Power	100-240 VAC, 50-60 Hz 2.5A Max
Operating Temp.	-31° to 50°C. (-24° to 122°F.)*
Non-op. Temp. (Off-mode with power applied)	-31° to 60°C. (-24° to 140°F.) The non-operating temperature feature requires power to be applied
Accessories Included	Water-resistant remote control with lithium battery Removable table top stand
TV Dimensions	815mm (W) x 562mm (H) with speakers, 509mm(H) w/o speakers x 160mm (D)
Weight	17.0 kg, 18.9kg w/speakers, 20.9kg w/ speakers and table top stand
Shipping Dimensions	939.8mm (W) x 787.4mm (H) x 297.18mm (D)
Shipping Weight	24.5 Kilograms
Warranty	One-year, in-factory, parts and labor
Warranty	One-year, in-factory, parts and labor

^{*}Temperature range is for operation in shaded location. Specifications may be subject to change.

Patent pending. All rights reserved. (C) 2009 SunBriteTV® LLC

HERMA




Designed with a durable **All-weather Environmental Feature-Set**, SunBriteTV televisions are engineered for permanent outdoor installation:


- The extra bright 32-inch HD 1366 x 768 LCD screen is integrated into an all-weather exterior that protects the internal components from rain, dirt, insects and scratches.
- **Dual-fan Airflow System** keeps the unit cool and dry in temperatures up to 50 degrees C.
- Internal Thermostatically-Controlled Heater protects TV in temperatures as low as -31 degrees F.
- Innovative Water-tight Cable Entry System with pass-through design keeps cables
 dry and allows for easy hook-ups.
- **Anti-Reflective Window** reduces glare, increases contrast and protects the LCD screen.
- The Detachable Speaker Module, control buttons and remote control are also water-resistant.

The **Control Feature-Set** maximizes system integration and programming security:

- RS232 and Discrete IR input connectors simplify control functions.
- The **Concealed IR Emitter** is located in the cable-entry compartment, thus protecting it from the elements.
- Remote Control Lock-out prevents unauthorized users from changing the programming.
- **Sleep Mode** automatically turns the TV to the Off mode when the signal is removed, and turns it back to On when the signal is restored.

SunBriteTV Model SB3220HD (All dimensions are in millimeters)





815mm (W) x 562mm (H) x 160mm (D)

Height dimension with table top stand is 593mm.

Deoth dimension with table top stand is 274mm.

Depth dimension with table top stand is 274mm.

TV with optional wall mount measures 229mm when folded flush against the wall.

Optional Accessories

SB-CM32A12	Ceiling mount with tilt. Includes adjustable extension column provides 76.2mm - 228.6mm above unit to ceiling in 25.4mm(1") increments without disassembly, and 101.6mm x 101.6mm designer ceiling plate. Meets VESA standards.
SB-WM32	Articulating wall mount with tilt and swivel, and extends up to 301.625mm from the wall. Meets VESA standards.
SB-DP2332X	Deck/Planter pole (requires purchase of wall mount). Special order item.
SB-FMT32	RadioFM™ transmits audio from TV to FM radio
SB-DC322	Outdoor TV dust cover